

▶ ABC DRY POWDER EXTINGUISHERS



ABC Dry Powder is multi purpose for all A, B, C and Electrical fire risks. Fullblaze ABC dry powder extinguishers are filled with high performance ABC powder and ideal for residential, commercial and industrial applications.

- ✓ High UV resistant polyester coating for extra protection from extremely harsh elements.
- ✓ Easy squeeze-grip operation and all metal handles.
- ✓ Complete with metal brackets (1,2 kg models with vehicle brackets).
- ✓ Heavy duty brackets for marine and truck applications are optional.
- ✓ Desigend and approved to EN3.
- ✓ Factory filled with high versatile ABC dry powder for great fire knock down.



TECHNICAL DATA

Model	FBPD1A	FBPD1E	FBPD1	FBPD1S	FBPD2S
Propellant Type	Stored Pressure				
Extinguishing Medium	ABC Powder	ABC Powder	ABC Powder	ABC Powder	ABC Powder
Capacity(kg)	1	1	1	1	2
Height(mm)	315	315	315	315	383
Shell Diameter(mm)	80	85	85	85	110
Working Pressure(bar)	15				
Test Pressure(bar)	27				
Full Weight(kg)	1.40	1.90	1.90	1.90	3.60
Discharge Time Approx.(second)	7.5	6.5	6.5	6.5	13.5
Temperature Range	-30°C - +60°C	-30°C - +60°C	-30°C - +60°C	-30°C - +60°C	-30°C - +60°C
Fire Rating	8A 34B C	8A 34B C	8A 34B C	8A 55B C	13A 89B C
Approved to EN3	✓	✓	✓	✓	✓



LPCB Ref. No. 1092Ea

▶ ABC DRY POWDER EXTINGUISHERS

ABC Dry Powder is multi purpose for all A, B, C and Electrical fire risks. Fullblaze ABC dry powder extinguishers are filled with high performance ABC powder and ideal for residential, commercial and industrial applications.

- ✔ Desigend and approved to EN3.
- ✔ Factory filled with high versatile ABC dry powder for great fire knock down.
- ✔ High UV resistant polyester coating for extra protection from extremely harsh elements.
- ✔ Easy squeeze-grip operation and all metal handles.
- ✔ Heavy duty brackets for marine and truck applications are optional.



TECHNICAL DATA

Model	FBPD3S	FBPD4S	FBP6S	FBPD9S	FBPD12
Propellant Type	Stored Pressure				
Extinguishing Medium	ABC Powder	ABC Powder	ABC Powder	ABC Powder	ABC Powder
Capacity(kg)	3	4	6	9	12
Height(mm)	480	490	540	558	672
Shell Diameter(mm)	130	130	154	182	190
Working Pressure(bar)			15		
Test Pressure(bar)			27		
Full Weight(kg)	5.20	6.80	9.30	13.70	17.40
Discharge Time Approx.(second)	15	17	17	19	30
Temperature Range	-30°C - +60°C	-30°C - +60°C	-30°C - +60°C	-30°C - +60°C	-30°C - +60°C
Fire Rating	21A 113B C	27A 144B C	43A 233B C	55A 233B C	155A 233B C
Approved to EN3	✔	✔	✔	✔	✔



LPCB Ref. No. 1092Ea