

► CO2 EXTINGUISHERS

Fullblaze CO2 fire extinguishers leave no residue after discharge, therefore they are ideal for B and electrical fire risks involving electrical equipment in residential, commercial and industrial environments like computer rooms, data storage centers etc.

- ✓ Designed and approved to EN3.
- ✓ Clean with no harm to machinery equipment.
- ✓ High UV resistant polyester coating for extra protection from extremely harsh elements.
- ✓ Chrome plated valve with pressure release mechanism.
- ✓ Fitted with anti electrostatic hose & horn for effective discharge.
- ✓ Complete with metal wall brackets.
- ✓ Heavy duty brackets for marine and truck applications are optional.

TECHNICAL DATA

Model	FBCD2	FBCD2A	FBCD5	FBCD5A
Body Material	Steel	Aluminium	Steel	Aluminium
Extinguishing Medium	CO2	CO2	CO2	CO2
Capacity(kg)	2	2	5	5
Height(mm)	565	545	745	675
Shell Diameter(mm)	103	111	136	152
Working Pressure(bar)	150	150	150	150
Test Pressure(bar)	250	250	250	250
Full Weight(kg)	620	5.00	14.40	12.00
Discharge Time Approx.(second)	6	6	9	9
Temperature Range	-30°C - +60°C	-30°C - +60°C	-30°C - +60°C	-30°C - +60°C
Fire Rating	34B	34B	70B	70B
Approved to EN3	✓	✓	✓	✓



CE EN3



LPCB Ref. No. 1092Ea

FullBlaze Middle East FZC New Expansionist Area Zarqa Free Zone Jordan

T: + 962 6 4893372 / 962 6 4893375

F: + 962 6 4893372

E-mail: sales@fullblaze-me.com

www.fullblaze-me.com