

# ▶ FOAM EXTINGUISHERS

Fullblaze Foam fire extinguishers provide a cleaner and also same effective alternative to dry powder extinguishers for class A and B fire risks.

- ✓ Desigend and approved to EN3.
- ✓ All models except FBFM1S are tested to clause 9.2 of EN7-3 for use on live electrical equipment.
- ✓ FBFM1S is technicall approved to EN7-3 except clause 6.1 which states the minimum charge for water based extinguishers shall be 2 Litre.
- ✓ High UV resistant polyester coating for extra protection from extremely harsh elements.
- ✓ Polyethylene lined cylinders for corrosion resistance.
- ✓ Easy squeeze-grip operation and all metal handles.
- ✓ Complete with metal brackets (2 , 1 Litre models with vehicle brackets).
- ✓ Heavy duty brackets for marine and truck applications are optional.



## TECHNICAL DATA

| Model                          | FBFM1S          | FBFM2S       | FBFM3S       | FBFM6S       | FBFM9S       |
|--------------------------------|-----------------|--------------|--------------|--------------|--------------|
| Propellant Type                | Stored Pressure |              |              |              |              |
| Extinguishing Medium           | AFFF Foam       | AFFF Foam    | AFFF Foam    | AFFF Foam    | AFFF Foam    |
| Capacity(kg)                   | 1               | 2            | 3            | 6            | 9            |
| Height(mm)                     | 335             | 403          | 438          | 537          | 620          |
| Shell Diameter(mm)             | 85              | 110          | 130          | 162          | 182          |
| Working Pressure(bar)          | 15              |              |              |              |              |
| Test Pressure(bar)             | 27              |              |              |              |              |
| Full Weight(kg)                | 1.90            | 3.60         | 5.20         | 9.60         | 14.00        |
| Discharge Time Approx.(second) | 8               | 15           | 20           | 22           | 30           |
| Temperature Range              | -5 C - +60 C    | -5 C - +60 C | -5 C - +60 C | -5 C - +60 C | -5 C - +60 C |
| Fire Rating                    | 5A 34B          | 8A 55B       | 13A 89B      | 21A 144B     | 27A 233B     |
| Approved to EN3                | ✓               | ✓            | ✓            | ✓            | ✓            |



CE EN3 



LPCB Ref. No. 1092Ea